



Commercial Series | Series 452

Commercial Sliding Window

Single Glazed

Window ID	Glass Type	Uw	SHGCw	Tvw	Inf
AWS-047-01	4SnClr	5.5	0.50	0.54	1.61
AWS-047-02	6SnClr	5.4	0.49	0.54	1.61
AWS-047-03	6EVanBG	5.2	0.37	0.45	1.61
AWS-047-04	6EVanClr	5.2	0.51	0.53	1.61
AWS-047-05	6EVanGy	5.2	0.34	0.25	1.61
AWS-047-06	6EVanSpB	5.2	0.30	0.31	1.61
AWS-047-07	6EVanSpGn	5.2	0.30	0.38	1.61
AWS-047-08	6.38VLam	6.6	0.66	0.71	1.61
AWS-047-09	6.38VLamGy	6.7	0.30	0.10	1.61
AWS-047-10	6.38TLam	6.7	0.34	0.26	1.61
AWS-047-11	6.38SnClr	5.4	0.47	0.53	1.61
AWS-047-12	6.38SnGy	5.4	0.36	0.25	1.61
AWS-047-13	6.38Sct	5.1	0.55	0.64	1.61
AWS-047-14	6.38CPNtrl	5.1	0.42	0.47	1.61
AWS-047-15	6.38CPClr	5.0	0.56	0.65	1.61
AWS-047-16	6.38CPGn	5.0	0.41	0.56	1.61
AWS-047-17	6.38CPGy	5.0	0.41	0.31	1.61
AWS-047-18	10.38ClrLam	6.7	0.48	0.48	1.61
AWS-047-19	10.38SnClr	5.6	0.42	0.47	1.61
AWS-047-20	10SnClr	5.3	0.39	0.43	1.61
AWS-047-21	10.38TLam	5.3	0.39	0.43	1.61
AWS-047-22	10.38GyLam	6.7	0.21	0.08	1.61

NOTES
 1. Uw is the whole window U-value. 2. SHGCw is the whole window solar heat gain coefficient. 3. Tvw is the whole window visible (light) transmittance
 4. Percentage improvement figures are compared with using base-case Generic Window 1 (3mm clear in standard aluminium frame). 5. A negative percentage improvement figure indicates performance worse than the base-case window. 6. A positive percentage improvement figure indicates performance better than the base-case window. 7. Maximum air infiltration is 5.0L/s.m2 at a positive pressure difference of 75 Pa as measured according to AS 2047. 8. Static performance (Uw SHGCw Tvw Tdw) calculated using Window 5.2 and Therm 5.2 software (LBNL), 2000-2003. 9. Annual energy performance (stars and % improvements) calculated using Nationwide House Energy Rating Software (AccuRate) according to procedures of WERS 2008. 10. Results disclosed at National Fenestration Rating Council (NFRC) regulations.



Commercial Series | Series 452

Commercial Sliding Window

Double Glazed

Window ID	Glass Type	Uw	SHGCw	Tvw	Inf
AWS-047-23	3/12Ar/3ET	3.9	0.53	0.53	1.61
AWS-047-24	3SG/12/3	4.6	0.39	0.49	1.61
AWS-047-25	4Az/10/4ET	4.1	0.31	0.44	1.61
AWS-047-26	4/10/4	4.6	0.55	0.57	1.61
AWS-047-27	4/10/4ET	4.1	0.51	0.53	1.61
AWS-047-28	4/10Ar/4ET	3.9	0.52	0.53	1.61
AWS-047-29	4SnClr/10/4	4.2	0.40	0.44	1.61
AWS-047-30	4SnClr/10Ar/4	4.1	0.40	0.44	1.61
AWS-047-31	5/8/5	4.7	0.54	0.57	1.61
AWS-047-32	5SG/8Ar/5ET	4.0	0.31	0.43	1.61
AWS-047-33	6.38CPClr/8/4	4.2	0.45	0.53	1.61
AWS-047-34	6.38CPClr/8Ar/4	4.0	0.45	0.53	1.61
AWS-047-35	6.38CPGy/8/4	4.2	0.33	0.25	1.61
AWS-047-36	6.38CPGy/8Ar/4	4.0	0.32	0.25	1.61
AWS-047-37	6SnClr/10/6	4.2	0.38	0.43	1.61
AWS-047-38	6SnClr/10Ar/6	4.0	0.38	0.43	1.61
AWS-047-39	10SnClr/6/6	4.5	0.37	0.42	1.61
AWS-047-40	10SnClr/6Ar/6	4.3	0.37	0.42	1.61

NOTES
 1. Uw is the whole window U-value. 2. SHGCw is the whole window solar heat gain coefficient. 3. Tvw is the whole window visible (light) transmittance
 4. Percentage improvement figures are compared with using base-case Generic Window 1 (3mm clear in standard aluminium frame). 5. A negative percentage improvement figure indicates performance worse than the base-case window. 6. A positive percentage improvement figure indicates performance better than the base-case window. 7. Maximum air infiltration is 5.0L/s.m2 at a positive pressure difference of 75 Pa as measured according to AS 2047. 8. Static performance (Uw SHGCw Tvw Tdw) calculated using Window 5.2 and Therm 5.2 software (LBNL), 2000-2003. 9. Annual energy performance (stars and % improvements) calculated using Nationwide House Energy Rating Software (AccuRate) according to procedures of WERS 2008. 10. Results disclosed at National Fenestration Rating Council (NFRC) regulations.