



## Commercial Framing | Series 607

### Single Glazed FaceLINE™ Framing

#### Single Glazed

Window ID	Glass Type	Uw	SHGCw	Tvw	Inf
AWS-044-01	4SnClr	4.3	0.55	0.60	0.20
AWS-044-02	6SnClr	4.3	0.54	0.59	0.20
AWS-044-03	6EVanBG	4.1	0.41	0.49	0.20
AWS-044-04	6EVanClr	4.1	0.56	0.58	0.20
AWS-044-05	6EVanGy	4.1	0.37	0.28	0.20
AWS-044-06	6EVanSpB	4.1	0.33	0.34	0.20
AWS-044-07	6EVanSpGn	4.1	0.33	0.42	0.20
AWS-044-08	6.38VLam	5.7	0.73	0.78	0.20
AWS-044-09	6.38VLamGy	5.7	0.32	0.11	0.20
AWS-044-10	6.38TLam	5.7	0.37	0.29	0.20
AWS-044-11	6.38SnClr	4.2	0.52	0.59	0.20
AWS-044-12	6.38SnGy	4.2	0.39	0.28	0.20
AWS-044-13	6.38Sct	3.9	0.61	0.71	0.20
AWS-044-14	6.38CPNtrl	3.9	0.46	0.51	0.20
AWS-044-15	6.38CPClr	3.9	0.61	0.72	0.20
AWS-044-16	6.38CPGn	3.9	0.46	0.62	0.20
AWS-044-17	6.38CPGy	3.9	0.45	0.34	0.20
AWS-044-18	10SnClr	4.3	0.52	0.58	0.20
AWS-044-19	10.38LamClr	5.6	0.57	0.59	0.20
AWS-044-20	10.38LamGy	5.6	0.25	0.10	0.20
AWS-044-21	10.38Tlam	3.9	0.46	0.53	0.20
AWS-044-22	10.38SnClr	4.8	0.51	0.57	0.20

NOTES  
 1. Uw is the whole window U-value. 2. SHGCw is the whole window solar heat gain coefficient. 3. Tvw is the whole window visible (light) transmittance  
 4. Percentage improvement figures are compared with using base-case Generic Window 1 (3mm clear in standard aluminium frame). 5. A negative percentage improvement figure indicates performance worse than the base-case window. 6. A positive percentage improvement figure indicates performance better than the base-case window. 7. Maximum air infiltration is 5.0L/s.m2 at a positive pressure difference of 75 Pa as measured according to AS 2047. 8. Static performance (Uw SHGCw Tvw Tdw) calculated using Window 5.2 and Therm 5.2 software (LBNL), 2000-2003. 9. Annual energy performance (stars and % improvements) calculated using Nationwide House Energy Rating Software (AccuRate) according to procedures of WERS 2008. 10. Results disclosed at National Fenestration Rating Council (NFRC) regulations.